



Europäisches
Patentamt

European
Patent Office

Office européen
des brevets



Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-
gen stimmen mit der
ursprünglich eingereichten
Fassung der auf dem näch-
sten Blatt bezeichneten
europäischen Patentanmel-
dung überein.

The attached documents
are exact copies of the
European patent application
described on the following
page, as originally filed.

Les documents fixés à
cette attestation sont
conformes à la version
initialement déposée de
la demande de brevet
européen spécifiée à la
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

98202656.9

BEST AVAILABLE COPY

CERTIFIED COPY OF
PRIORITY DOCUMENT

Der Präsident des Europäischen Patentamts:
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

DEN HOF, DEN

THIS PAGE BLANK (USPTO)



Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

Blatt 2 der Bescheinigung
Sheet 2 of the certificate
Page 2 de l'attestation

Anmeldung Nr.:
Application no.: 98202656.9
Demande n°:

Anmeldetag:
Date of filing: 07/08/98
Date de dépôt:

Anmelder:
Applicant(s):
Demandeur(s):
Koninklijke Philips Electronics N.V.
5621 BA Eindhoven
NETHERLANDS

Bezeichnung der Erfindung:
Title of the invention:
Titre de l'invention:

Demonstrating an effect of a signal processing operation of a signal processing device

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s) revendiquée(s)

Staat:
State:
Pays:

Tag:
Date:
Date:

Aktenzeichen:
File no.
Numéro de dépôt:

Internationale Patentklassifikation:
International Patent classification:
Classification internationale des brevets:

/

Am Anmeldetag benannte Vertragsstaaten:
Contracting states designated at date of filing: AT/BE/CH/CY/DE/DK/ES/FI/FR/GB/GR/IE/IT/LI/LU/MC/NL/PT/SE
Etats contractants désignés lors du dépôt:

Bemerkungen:
Remarks:
Remarques:

THIS PAGE BLANK (USPTO)

Demonstrating an effect of a signal processing operation of a signal processing device.

FIELD OF THE INVENTION

The invention relates to a device for demonstrating an effect of a selected signal processing operation as defined in the preamble of Claim 1. The invention further relates to an apparatus as defined in the preamble of Claim 8, a television receiver as defined in the preamble of Claim 10 and a method for demonstrating an effect of a selected signal processing operation as defined in the preamble of Claim 11.

BACKGROUND OF THE INVENTION

An apparatus as defined above is disclosed in EP 0 417 728 A2. The known apparatus, e.g. a television receiver or a video recorder, comprises a user operable control circuit for generating a sequence of commands which cause a number of functions of the apparatus to be invoked consecutively. Examples of functions invoked by the control circuit are picture-in-picture, zoom-effect, mosaic screen and features for enhancing the picture quality, such as noise filters, cross-color and interference reduction. The effects of the functions invoked by the control circuit are observable on the television screen, giving a potential buyer of the apparatus an impression of its functions.

A disadvantage of the known apparatus is that the effectiveness of the demonstration of said functions heavily depends on the video content being received at the time of the demonstration.

OBJECT AND SUMMARY OF THE INVENTION

It is an object of the invention to provide a device for demonstrating an effect of a selected signal processing operation as defined above which provides an improved demonstration of the signal processing operation. To this end, a first aspect of the invention provides a device as claimed in Claim 1. A second aspect of the invention provides an apparatus as claimed in Claim 8. A third aspect of the invention provides a television receiver as claimed in Claim 10. A fourth aspect of the invention provides a method as claimed in Claim 11. Advantageous embodiments of the invention are defined in the dependent claims.

The device for demonstrating an effect of a selected signal processing operation as claimed in Claim 1 comprises a signal processing device for processing incoming signals to obtain processed signals, and demonstration means, similar to the control circuit of the known apparatus, for demonstrating the effects of the processing device. A user command selects which signal processing operation will be performed by the processing device. As an example, the processing device may be a video signal processor for processing an incoming video signal to obtain RGB signals to be supplied to a display. The user command may switch on a black-stretch feature or a noise reduction operation. Dependent on the processing operation demonstrated, a specific portion of demonstration content which is most suited for demonstrating the effect of said processing operation is retrieved from the storage means and processed by the signal processing device before being presented on the presentation means. In this way it is achieved that the effect of the processing operation is demonstrated more effectively, thus convincing potential buyers of the quality of the device.

In an embodiment of the invention as claimed in Claim 2, switching means select the demonstration signals or the incoming signals to be processed by the signal processing device in response to the user command and presented on the presentation means, thus excluding any conditions caused by the incoming signals which may diminish the effectiveness of the demonstration.

In an embodiment of the invention as claimed in Claim 3, the signal processing device is adapted to process video signals which are presented on a display screen, said processing operation being conceived, for example, to enhance the quality of the pictures displayed. For demonstrating such a feature, a static picture especially suited for demonstrating the effect of that feature is retrieved from the storage means and presented on the display screen. For example, when demonstrating a black-stretch feature, a picture comprising grey areas is presented, and when demonstrating a comb-filter, a picture comprising patterns of fine black and white lines is presented. For demonstrating features which are intended to improve a presentation involving moving pictures, e.g. Natural Motion, a sequence of pictures can be stored in the storage means and presented consecutively as a moving video presentation. Such a moving video presentation can be iterated a number of times, to give the viewer multiple opportunities to appreciate the effect of the feature.

In an embodiment of the invention as claimed in Claim 6, it is achieved that the viewer can easily perceive the difference between the apparatus having the demonstrated feature and an apparatus not having that feature. In the case of video content, this difference can be alternatively demonstrated by presenting the demonstration signals in a split-screen

form, which enables the viewer to perceive the difference at a glance. The viewer could also be enabled to activate and deactivate the feature by hand during the demonstration.

In an embodiment of the invention as claimed in Claim 9 said user command comprises the operation of control means which are dedicated to control functions of the apparatus which are different from the demonstration function. Modern appliances such as VCRs and TVs often have a remote control for controlling most of the functions. The appliances themselves have only a few buttons for controlling the major functions, such as channel selection and volume control. A dedicated button for activating the demonstration is not desirable, since production costs would increase and the demonstration function should be preferably known to shop personnel only. This embodiment makes the demonstration function available through the operation of a particular combination of regular control buttons of the appliance, e.g. by pressing the volume up and down buttons simultaneously, possibly for a predetermined period of time, e.g. 5 seconds. In this way it is avoided that visitors who are not seriously interested in buying the appliance start the demonstration.

The invention is particularly suitable for a television receiver, the presentation means being the television screen or the loudspeakers, or for any other apparatus having a video output signal, such as a video recorder or DVD player, the presentation means being a built-in display or the screen of a connected television receiver. The invention is further applicable, for example, to audio equipment, the presentation means being the loudspeakers.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other aspects of the invention will be apparent from and elucidated by way of a non-limitative example with reference to a figure which shows a television receiver as an embodiment of the apparatus according to the invention;

DESCRIPTION OF EMBODIMENTS

The figure shows a television receiver for receiving TV signals which are obtained via an antenna or cable network 1. A tuner 2 selects one of the received signals and demodulates it. Audio and video information from the selected signal is further processed in a signal processor 3 which comprises an audio processor 4 and a video processor 8. The audio information is processed by the audio processor 4 and presented by a speaker 5. The video information is processed by the video processor 8 and presented on a display screen 9. A control unit 6 enables a user to enter commands which are processed by a microprocessor 7. For example, the microprocessor 7 relays commands to the tuner for selecting a TV signal, and

commands to the signal processor 3 for controlling sound and picture parameters.

Furthermore, the microprocessor 7 is adapted to send audio and video information to the signal processor 3, and to control a signal switch 12, which initially selects the signals from the tuner 2 as input signals to the signal processor 3. A memory 10 is provided for storing the microprocessor instructions for performing the various functions of the television receiver. One of the functions implemented this way is a demonstration function, the memory 10, the microprocessor 7 and the signal switch 12 thus constituting the demonstration means. The control unit 6 comprises a remote control unit (not shown) for receiving infrared signals from a remote control and a few buttons for controlling some major functions of the television receiver. The control unit 6 comprises, inter alia, a volume-up button 6a and a volume-down button 6b which enable the user to turn the volume up and down, respectively. When the user pressed both the volume-up button 6a and the volume-down button 6b simultaneously for 5 seconds, the demonstration function is activated. Initially a menu is displayed on the display screen 9 presenting a number of features which can be demonstrated, and an exit button for leaving the demonstration function. When the user selects one of the features the picture information which is most suitable for demonstrating the selected feature is read from a memory 11, and the signal switch 12 is controlled in such a way that the picture information is selected as input signals to the signal processor 3. For example, in the case of demonstrating a black-stretch feature, a picture comprising grey areas is presented. When a feature is selected which is intended to improve a presentation involving moving pictures, e.g. Natural Motion, a sequence of pictures is read from the memory 11 and presented consecutively as a moving video presentation. The moving video presentation is iterated a few times, giving the viewer multiple opportunities to appreciate the effect of the feature. As an example, the demonstration starts with the selected feature deactivated. After two seconds the selected feature is activated, after another two seconds the selected feature is deactivated again, etc. This process is repeated a predetermined number of times after which the demonstration stops. Further signals, e.g. displayed or spoken text, could be provided to indicate which feature was selected and whether the selected feature is activated or deactivated at a particular moment.

Pressing either of the volume-up button 6a or the volume-down button 6b stops the demonstration, and the microprocessor 7 controls the signal switch 12 to select the signals from the tuner 2 as input signals to the signal processor 3.

Although the invention has been described with reference to particular illustrative embodiments, variations and modifications are possible within the scope of the inventive concept. Thus, for example, storage means could be applied which are incorporated in a separate device connected in some way to the apparatus. Instead of demonstration content which is ready to be presented, the storage means could contain the content in an encoded or compressed form, e.g. an algorithm for generating a graphical picture which is particularly suited for showing the effect of the demonstrated feature. The memory 11 may be any storage device, such as a floppy disk or a hard disk, and may be combined with the memory 10. The user command need not comprise the operation of buttons on the apparatus, but could also be entered by means of one or more buttons on a remote control, or by means of a joystick or a mouse.

Although the embodiments are directed to video processing in a TV, the invention is also suitable for audio processing, or for signal processing in other apparatuses which have to present information, such as VCRs, computer monitors etc.

15

Summarizing, the invention relates to a device for demonstrating an effect of a selected signal processing operation. The device comprises signal processing means (3) for processing incoming signals to supply said signals to presentation means (9), and demonstration means (7, 10, 12) for demonstrating the selected processing operation. The device further comprises storage means (11) for storing a demonstration signal which is specifically suitable for effectively demonstrating the feature. Upon activation of the demonstration means, a demonstration signal which is most suitable for demonstrating said processing operation is read from the storage means, processed by the signal processing means and presented on the presentation means.

CLAIMS:

1. A device for demonstrating an effect of a selected signal processing operation, said device comprising a signal processing device for processing an incoming signal to supply a processed signal to presentation means, and demonstration means for controlling the signal processing device to perform said selected signal processing operation in response to a user command, **characterized in that** the demonstration means further comprise storage means for the storage of a demonstration signal selected so as to enable an effective demonstration of the particular processing operation, and directing means for directing the demonstration signal to the signal processing device in response to said user command.
2. A device according to claim 1, **characterized in that** the directing means comprise switching means for supplying, in response to said user command, either the incoming signals or the demonstration signals to the signal processing device.
3. A device according to claim 1 or 2, said incoming signals being video signals and said presentation means comprising a display screen, **characterized in that** the storage means are adapted to contain a static picture.
4. A device according to claim 3, **characterized in that** the storage means are adapted to contain further pictures, the demonstration means being adapted to present said picture and said further pictures consecutively as a moving video presentation.
5. A device according to claim 4, **characterized in that** the demonstration means are further adapted to repeat the moving video presentation automatically.
6. A device according to any of the claims 1 to 5, **characterized in that** the demonstration means are further adapted to activate and deactivate said processing operation alternately during the presentation of the demonstration signals.

7. A device according to any of the claims 3 to 5, **characterized in that** the demonstration means are further adapted to present the demonstration signals in a split-screen form, one part of the display screen showing a presentation of the demonstration signals having said processing operation activated and another part of the display screen showing a presentation of the demonstration signals having said processing operation deactivated.
8. An apparatus for processing an audio or video signal, comprising a device according to any of the claims 1 to 7.
9. An apparatus according to claim 8, comprising a number of user operable means for controlling functions of the apparatus, **characterized in that** said user command comprises the operation of a single one or a combination of said control means for a predetermined period of time.
10. A television receiver as an apparatus according to claim 8 or 9.
11. A method for demonstrating an effect of a selected signal processing operation, the method comprising the steps of processing an incoming signal to supply a processed signal to presentation means, and controlling said selected signal processing operation to be performed in response to a user command, **characterized in that** the method comprises a step of reading a demonstration signal from storage means, which demonstration signal has been selected so as to enable an effective demonstration of said selected processing operation and a step of processing the demonstration signal in response to said user command.


ABSTRACT:

The invention relates to a device for demonstrating an effect of a selected signal processing operation. The device comprises signal processing means (3) for processing incoming signals to supply said signals to presentation means (9), and demonstration means (7, 10, 12) for demonstrating the selected processing operation. The device further comprises storage means (11) for storing a demonstration signal which is specifically suitable for effectively demonstrating the feature. Upon activation of the demonstration means, a demonstration signal which is most suitable for demonstrating said processing operation is read from the storage means, processed by the signal processing means and presented on the presentation means.

10

Fig.

1/1



THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)